



Plant Products

Industrial Supplier



Pushbutton DRT



Control Stations

Built-in components pushbutton



DRT 1 x 2-pole



DRT 4 x 1-pole



DDT 2 x 1-pole



DDT 2 x 2-pole

Technical data

Ex-pushbutton DRT and double pushbutton DDT

Marking accd. to 2014/34/EU	⊕ II 2 G Ex de IIC/IIB Gb / ⊕ I M2 Ex de I Mb
EC-Type Examination Certificate	IBExU 14 ATEX 1030 U
IECEX Certificate of Conformity	IECEX IBE 14.0005U
Marking accd. to IECEx	Ex de IIC Gb Ex de IIB Gb Ex de I Mb
Operating temperature	-45 °C up to +80 °C (IIC) -60 °C up to +80 °C (IIB)
Application temperature ¹⁾	-45 °C up to +55 °C (IIC) -60 °C up to +55 °C (IIB)
Rated voltage	500 V AC
Rated current	16 A
Rated current with gold contact points	0.4 A
Rated making-/rated breaking capacity accd. EN 60947-5-1	AC-15: U_e 250 V / I_e 6 A U_e 500 V / I_e 4 A DC-13: U_e 24 V / I_e 6 A U_e 220 V / I_e 1 A
Degree of protection accd. to EN 60529	IP66 (installed condition)
Type of mounting	DIN rail mounting
Enclosure colour	grey
Gasket material	Neoprene (standard), Fluorsilikon or Viton on request

2-pole version

Connecting terminals	2 x 2.5 mm ²
Dimensions (L x W x H)	59 x 31 x 45 mm
Weight	0.15 kg

4-pole version²⁾

Connecting terminals	4 x 2.5 mm ²
Dimensions (L x W x H)	59 x 73 x 45 mm
Weight	0.35 kg

¹⁾ The limits of the operating temperature range and the max. permissible temperature rise of the components have to be taken into account. See also pages 2.4.34/35.

²⁾ The 4-pole pushbutton needs two mounting areas. The actuator will be in the middle of the two mounting areas.

Built-in components pushbutton



DDT 2 x 2-pole



DDT 2 x 1-pole



DRT 4 x 1-pole



DRT 1 x 2-pole

Ordering code for component (Code 2)

Code	Component	Code			
A	Pushbutton, for enclosure mounting	DRT			
	Double pushbutton, for enclosure mounting	DDT			
Code	Circuit	Contacts		Code	
		DRT	DDT	silver contact points	gold contact points
C	2 NC			13	16
	2 NO			14	17
	1 NO + 1 NC			15	18
	4 NC			20	25
	1 NC + 3 NO			21	26
	2 NC + 2 NO			22	27
	3 NC + 1 NO			23	28
	4 NO			24	29

Built-in components pushbutton



DRT 1 x 2-pole



DRT 4 x 1-pole



DDT 2 x 1-pole



DDT 2 x 2-pole

Ordering code for component (Code 2)

Code	Label	Inscription	Code	Inscription	Code
D1, D2		0, I, Start, Stop	001	0	002
		I	003	I I	004
		☹	005	STOP	006
		START	007	emergency stop	008
		LANGSAM	009	SCHNELL	010
		EMERG.STOP	011	➔	012
		ARRET	014	MARCHE	015
		AUF	016	AB	017
		Neutral white	018	Neutral green	019
		0, I, Arret, Marche	020	UP	024
		DOWN	025	ZU	026
		ON	027	OFF	028
		+	030	-	031
		Neutral rot	033	Neutral yellow	034
		EIN	036	AUS	037
		AUTO	039	HAND	050
		SENKEN	051	HEBEN	052
		LINKS	053	RECHTS	054
		FAST	055	SLOW	056
		RESET	057	OPEN	058

Built-in components pushbutton



DDT 2 x 2-pole



DDT 2 x 1-pole



DRT 4 x 1-pole



DRT 1 x 2-pole

Ordering code for component (Code 2)

Content	Circuit	Code	Ordering code				
			A	B	C	D1	D2
Pushbutton with silver contact points							
Version with standard label (0, I, START, STOP)							
2 NC	2 NC	13	DRT	0	13	001	---
2 NO	2 NO	14	DRT	0	14	001	---
1 NO + 1 NC	1 NO + 1 NC	15	DRT	0	15	001	---
4 NC	4 NC	20	DRT	0	20	001	---
3 NO + 1 NC	3 NO + 1 NC	21	DRT	0	21	001	---
2 NO + 2 NC	2 NO + 2 NC	22	DRT	0	22	001	---
1 NC + 3 NO	1 NC + 3 NO	23	DRT	0	23	001	---
4 NO	4 NO	24	DRT	0	24	001	---

Double pushbutton with gold contact points

Version with standard label (0, I, START, STOP)							
2 NC	2 NC	16	DDT	0	16	001	001
2 NO	2 NO	17	DDT	0	17	001	001
1 NO + 1 NC	1 NO + 1 NC	18	DDT	0	18	001	001
4 NC	4 NC	25	DRT	0	25	001	001
3 NO + 1 NC	3 NO + 1 NC	26	DRT	0	26	001	001
2 NO + 2 NC	2 NO + 2 NC	27	DRT	0	27	001	001
1 NC + 3 NO	1 NC + 3 NO	28	DRT	0	28	001	001
4 NO	4 NO	29	DRT	0	29	001	001

Contact

Plant Products B.V.

Office +31 10 - 434 32 66

Wouter Pietersen

Mobile +31 6 - 432 02 745

E-mail w.pietersen@plantproducts.nl

Westhavenkade 98

3133 AV Vlaardingen

The Netherlands



www.PlantProducts.nl